

JETCEM RAPID SET SAND/CEMENT

DESCRIPTION

JETCEM is a specially formulated rapid setting cement based patching/repair compound which when mixed with water sets in about 30 minutes.

- Rapid setting (30 minutes, depending on ambient temperature and conditions).
- Easy mixing, just add water.
- Fills up to 25mm in one application (for deeper holes in excess of 25mm use Jetcem Premix sand/cement)

Colour	Product Code	Pack Size	Box Qty
Grey	SCEM003	2kg	6
	SCEM004	6kg	2



AREAS FOR USE

- Internal and external repairs to gaps and cracks and walls and floors.
- Repairing flags, slabs, stones and bricks.
- Patching steps and window sills.
- Pointing brick and stone.
- Jointing earthenware pipes and drains.
- Repairs to ponds and pools.
- Setting in W/C's and sinks.
- Leak sealing in concrete based surfaces.
- Setting railings and posts.

LIMITATIONS

- This product should not be used for load bearing applications.
- Do not use where chemical resistance is required.
- Repairs to fishponds etc – seal repair with a suitable paint before re-stocking.
- It is always the user's responsibility to determine suitability of use. If in doubt, request technical data or contact Technical Services department.


SURFACE PREPARATION

Before applying, ensure surfaces are clean, sound and free from dust, crumbly material or any contaminants, which may affect adhesion.

APPLICATION

- Thoroughly wet surfaces to improve adhesion.
- Always use a clean mixing vessel and add approx. 3 parts by volume powder to one part by volume clean cold water and mix immediately to a smooth, reasonably thick slump free paste. The mixed cement will remain workable for 5-10 minutes only.
MIX NO MORE CEMENT THAN CAN BE USED IN 5 MINUTES
- Press the cement into the repair with a trowel or filling knife.
- Once the product begins to stiffen, throw away the residue.
DO NOT ADD FURTHER WATER TO THE MIX. THIS WILL DESTROY STRENGTH.
- In warm conditions, cover Jetcem with polythene to assist cure.
- Clean tools etc with warm water before Jetcem dries.

- CONTINUED ON NEXT PAGE -



JETCEM RAPID SET SAND/CEMENT

STORAGE & PACKAGING

This product has a shelf life of 12 months if stored in its original unopened packaging in normal dry conditions. It is supplied in 10kg + 20kg multi-ply moisture resistant paper sacks.

PRECAUTIONS

For more information and precautions, refer to the safety data sheet.

NOTE

The information contained on this spec sheet is given voluntarily and in good faith. It is to the best of our knowledge true and accurate; however it may contain information which is inappropriate under certain conditions of use. The company cannot accept responsibility for any loss or damage due to inappropriate use or the possibility of variations of working conditions and of workmanship outside our control.

The user must ensure the product's suitability for the application intended and if in doubt should seek a written technical specification for the product's application.

Arc recommends the use of Marmox Tile Backer Boards and Showerlays for a rigid, 100% waterproof wall & floor tiling substrate.



Arc Building Products
IDA Business & Technology Park,
Ballynattin, Arklow,
Co. Wicklow, Ireland.

www.arcbuildingproducts.ie

Phone: +353 (0)402 41200

Phone: +353 (0)402 32370

Fax: +353 (0)402 24168

Email: sales@arcbuildingproducts.ie