

INSTANT SPRAY CONTACT ADHESIVE

DESCRIPTION

STICK 2 SPRAY CONTACT ADHESIVE is a sprayable glue which bonds to most common materials including wood, concrete, stone, tiles, rubber foam, metals, rigid plastics, polyethylene, canvas, fabrics, cardboard, paper and cork. Ideal for securing most carpets/floor coverings, the product is suitable for internal and external use giving excellent permanent or temporary adhesion, depending on method of application.

COLOUR	straw
BASE	Synthetic rubber/resin
SOLIDS	10%-20%
VISCOSITY	Low
COVERAGE	120-250g/m2
TACK LIFE	2-5mins
FLASH POINT	-40°C
SHELF LIFE	12 months at 4 - 25°C in original containers
CLEANER	Arc Foam Gun Cleaner



BENEFITS

- Good adhesion - fast rate of tack development.
- Ease of use - no messy spreading/clean up
- Time saving- easier and quicker than most trowel/spreader applied adhesives.
- Foaming formula - gives low soak in into most substrates.
- Halogen and CFC Free.

AREAS FOR USE


- Fixing carpets to most subfloors - eliminates the need for gripper rods
- Most joinery applications. Bonds all woods /composite board etc.
- Fixing most common laminate materials*
- Bonding metals to most surfaces.
- Bonds rubber, most plastics and leather
- As a general purpose household/hobby adhesive

LIMITATIONS

- Do not use on soft (plasticised) PVC.
- Do not use on polystyrene. Use EVERBUILD GUN A NAIL
- Do not use on cellulose painted surfaces
- Do not use on bitumen or tar leaching products.
- Medium strength adhesive - do not use on heavy/large/thick areas of laminate
- Use STICK 2 ALL PURPOSE CONTACT ADHESIVE.

SURFACE PREPARATION

The surfaces to be glued should be clean and free from dust, grease and other contaminants. Materials should be stored in a warm environment prior to bonding to avoid chilling of the glue line, which leads to extended setting times.



INSTANT SPRAY CONTACT ADHESIVE

DESCRIPTION

Shake the can well before use.

Select the fan width by turning the nozzle to the desired position. Spray adhesive from 6-8 inches away onto one or both surfaces; depending on the type of surface /strength of bond required.

The surfaces to be glued should be clean and free from dust, grease and other contaminants. Shake well before use. Select fan width by turning to desired setting. Spray adhesive from 6 to 8 inches (15 to 20 cms approx.) away onto one or both surfaces, depending on type of strength of bond required.

STRONG BONDING

Apply 1-3 coats (depending on strength required) to both surfaces. Allow solvent to evaporate (30 seconds) and press surfaces together from centre outwards.

TEMPORARY REPOSITIONABLE BONDING:

Spray on one surface only and allow to dry for 2-3 minutes before bonding. Excess adhesive can be removed with STICK 2 CONTACT ADHESIVE THINNER AND CLEANER. To prevent spray nozzle from blocking, at the end of each day, turn can upside down and press nozzle until spray is clear of adhesive.

Excess adhesive can be removed using EVERBUILD GUN FOAM CLEANER. To prevent spray nozzle from blocking,; at the end of each use, turn can upside down and press nozzle until spray is clear of adhesive.

The newly bonded materials should not be subjected to extreme temperature changes for 3 to 4 days after bonding. Avoid further fabrication until the adhesive has fully cured.

STORAGE

Store in original unopened containers between 4 and 25oC.
Store as flammable liquid.

SHELF LIFE

Twelve months from date of manufacture in original unopened containers.

HEALTH AND SAFETY




Extremely flammable
Possible risk of irreversible effects.
Keep out of reach of children.
Keep away from sources of ignition – NO SMOKING.
Do not breathe vapour or spray.



Wear suitable protective clothing, gloves, and eye/face protection.
If swallowed, seek medical advice immediately and show this container or label.
Use only in well ventilated areas.
Avoid exposure- obtain special instructions before use.

- CONTINUED ON NEXT PAGE -



INSTANT SPRAY CONTACT ADHESIVE

PRECAUTIONS

For more information and precautions for use refer to the safety data sheet.

NOTE

In case of doubt, we recommend you to contact our technical department, which will suggest the most appropriate adhesive for your purposes, or will conduct the test required to find it.

The technical information contained in this document, as well as our technical advice whether verbal or written, is the result of our experience with the product and should be considered as collaboration without compromise, since the use and / or final application of our adhesives is beyond our control, declining all liability for improper use. The customer is responsible to confirm and evaluate prior to use, by trial or test if the product conforms to required employment. The information, recommendations or advices contained herein are given in good faith, supplier makes no warranty or guarantee, express or implied, that the results described herein will be obtained under end-use conditions, or as to the effectiveness or safety of any design incorporating supplier's materials, products, services, recommendations or advice. Nothing in this or any other document shall alter, vary, supersede or operate as a waiver of any of the supplier's standard terms of sale.

So our guarantee is limited to ensure the quality of our products, according to our quality standards.



Arc Building Products
IDA Business & Technology Park,
Ballynattin, Arklow,
Co. Wicklow, Ireland.

www.arcbuildingproducts.ie

Phone: +353 (0)402 41200

Phone: +353 (0)402 32370

Fax: +353 (0)402 24168

Email: sales@arcbuildingproducts.ie