



Quick Drying Ready Mixed Filler **Technical Data Sheet**

Description

Bartoline Quick Drying Filler is ideal for filling small gaps and cracks up to 3mm in plaster, plasterboard, wood and brick. Ready mixed for easy application and simple to use. Has excellent adhesive properties which keep the filler firmly in position and allows a wide range of applications.

Directions

Ensure surfaces to be filled are clean, dry, sound and free from grease and dust. Touch in nail/screw heads with an oil-based paint to prevent rusting. Stir the filler to a smooth consistency. Work filler into the crack or hole and level off with a wet filling knife/scrapper. Wipe any excess filler using a damp cloth. When filler is dry it can be sanded to a smooth finish and painted or papered as required. Do not use externally when rain is imminent. When used outdoors protect filled area from rain/water until sealed with an oil-based paint. Do not use on surfaces regularly under water. After setting overnight the filler can be left unpainted or alternatively if painting over the repair use an oil-based paint before any further paint is applied. Dries white with a smooth finish. Replace lid after use.

Cleaning & Storage

All tools and mixing bowls should be cleaned with warm water before filler sets.
PROTECT FROM FROST.

Health and Safety

See MSDS for full information.

Technical Data

Measurement	Value	Test Method
Physical State	Paste	Visual
Colour	White	Visual
Odour	None	
Flash point	Not Applicable	
Viscosity	2800 - 3200	Helipath Spindle SF/Speed 10
pH	8.3 – 9.3	

Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
1Kg Tub	52729220	5010789729226	05010789388430	6	96	576	12	8

Customs Tariff Code

3214 1090

Shipping Classification

Non-Hazardous for shipping purposes