

Technical Data Sheet

Date of compilation: 13/08/2021

MOULD X CLEAR PROTECTIVE BARRIER

DESCRIPTION

Lasting protection against mould, fungi, algae and moss in problem areas with unfavourable humidity conditions and thermal bridging. Protects against the formation of new mildew. Odourless and therefore suitable for living room, bedroom and children's rooms. For walls with wallpaper, paint, tiles and masonry.



EFFECT

Lasting film protection to prevent mould formation in interior areas. Transparent and odourless liquid prevents formation of moulds and algae on problem surfaces with unfavourable air humidity conditions by film protection. Acts to inhibit mould forming and reduces the absorption of moisture.

AREAS OF USE

For all absorbent substrates such as wallpapered or painted walls, ceilings, tiles, grouting, plaster, concrete, brick, sand-lime brick, gypsum boards, wood, amongst others. Suitable for living rooms, bedrooms and children's rooms, basements, sanitary areas, kitchen, saunas. For places where mould infestation often occurs because of thermal bridges, such as e.g. window corners or behind furniture, cupboards, wall panelling. Treated areas can be wallpapered or painted afterwards.

DIRECTIONS FOR USE

Before application, ensure that any mould and spores which are present as well as green residues are thoroughly removed. For this purpose, use MouldX Mould Remover with Chlorine in sanitary areas or on washable surfaces, and MouldX Mould Remover Chlorine-free on absorbable surfaces. Allow cleaned surfaces to dry thoroughly. Then spray the anti-mould impregnation generously at a minimum distance of 1m over the endangered area covering well and allow to dry.

Important:

Always test for surface compatibility before use. Moulds and their spores present a serious danger to health. For this reason, they should be completely removed and measures should be taken to prevent new formulation. One cause of mould formation is increased air humidity, therefore, air out regularly (brief and intensively for 5 – 10 minutes with the window completely open) to enable an adequate exchange of air in the room.

Technical Data Sheet

Date of compilation: 13/08/2021

MOULDx CLEAR PROTECTIVE BARRIER

TECHNICAL INFORMATION

Property	Value
Density	1,00 g/ml
pH	≈ 8.0
Colour	Whitish liquid
Smell	Mild

PACKAGING, CONSUMPTION & STORAGE

Supplied in 750ml Spray Bottle (6units/box).

Depending on the absorbency of the surface, 750 ml are sufficient to treat an area of 10 – 15 m². Do not use below +5°C. Store in a cool but frost-free place! EU VOC limit value for this product (Cat.:A/g, Wb) = 30 g/l (2010).Content of product: < 15 g/l

HAZARD STATEMENTS

Causes skin irritation. Causes serious eye irritation.

SAFETY INSTRUCTIONS

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Wear protective gloves/ eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/attention. Dispose of contents/ container in accordance with local/ regional/ national/ international regulations.

ADDITIONAL SPECIFICATIONS

Use biocides safely. Always read the label and product information before use.

NOTE

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Full information and advice is freely available from our Technical Services Department e-mail technical@arcbuildingproducts.ie. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.