

Units 27-29 Gorey Business Park Ramstown, Gorey Co. Wexford, Ireland Tel: +353 (0)53 9483788 www.arcbuildingproducts.ie

TECHNICAL DATA SHEET

Date: Dec 2013 Version: 1001 Pages: 1

Arc Self Adhesive Scrim Tape

DESCRIPTION:

Self adhesive fibreglass plasterboard joint tape for taping joints, repairing cracks and patching holes.

USES:

For reinforcing joints, crack repairs and hole patches in plaster/plasterboard/drywall walls and ceilings.

PROPERTIES:

Easy to apply. High adhesion. Provides extra reinforcement.

INSTRUCTIONS:

Ensure surfaces are clean, free from dust and dry. Peel required amount of tape and press firmly into place. Cut with a knife.

TECHNICAL FEATURES:

Specification: 2.85×2.85 mm (9×9 count/25cm)

Colour: White

Warp of yarn: 33tex×2 Woof of yarn: 100tex Mesh size: 9 × 9 mesh Average of weight: ≥70g/m2

Tensile strength: Warp: 500N/50mm

Weft: 800N/50mm

Alkaline resistant Acrylic and adhesive acrylic total content: 30 %

Alkaline resistant resin: Acrylic resin.

Adhesive coating: Acrylic resin. It will keep strong sticky within 6 months.

Alkaline resistance properties: after 28 days immersion of 5% NaoH solution, the average retention rate for

tensile fracture strength ≥65%.

STORAGE:

Store between 5 to 30°C in unopened packaging.

PACKAGING:

50mm x 90m, 75mm x 90m and 100mm x 90m

SAFETY AND HYGIENE:

According to recent legislation, this product is risk free and does not require and special safety when handling or storing.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Arc Building Products products' are available for sale in accordance with Arc Building Products standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use, and any labour involved is beyond our control. Our warranty is therefore limited to the quality of supplied product.