

Art. Nr.: 20202 02750

WEPOS Colour Intensifer

Description:

For all absorbent natural and artificial stone surfaces. Colours look more intense and fresher, almost as if they were wet. The impregnation reduces the vulnerability to soiling, makes surfaces water repellent and increases resistance to stains. For interior and exterior use on floors, steps, house entrances, patios, balconies, window sills.

Effect:

Deepens and intensifies color and highlights texture without making it shiny. Surfaces look more brilliant and fresher, almost as if they were wet. The impregnation reduces stones' susceptibility to dirt, makes them waterresistant and reducing stains.

Application:

For all absorbent natural and artificial stone surfaces, concrete building blocks, exposed aggregate concrete, slate, marble, sandstone, terrazzo, porphyry, Solnhofen slabs, concrete surfaces, etc. that look faded or colorles. Can be used indoors and out, for floors, steps, foyers, terraces, balconies and windowsills. Also suitable for flamed or sawn granite.

Direction of use:

The base needs to be dry, unmarked and clean. Apply a thin, even layer using a paint roller or a brush. Do not apply more than the surface can absorb, and avoid leaving puddles. Avoid creating streaks. Drying time is about 30 minutes. Do not step on the surface during this time. Afterward, protect the impregnated surface from moisture for 2 days.

Important:

Impregnated surfaces must be completely dry before application. White marks that appear after drying indicate moisture in the stone. Application areas must also be protected from moisture from underneath. For larger surfaces, always work in sections. Cover glass and solvent-sensitive materials during the appli-cation. Do not process at temperatures below 10°C. Surfaces that are non-absorbent, polished or finely smoothed cannot be sealed.

Packing unit: 1000 ml-tin (4 per box)

Technical Information:

- Density: 0,79 g/ml
- PH: n.a.
- colour: transparent liquid
- smell: characteristic

Hazard statements:

Flammable liquid and vapour. May cause

drowsiness or dizziness. May be fatal if swallowed and enters airways.

Safety instructions:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/ sparks/ open flames/ hot surfaces. -No smoking. Use only outdoors or in a wellventilated area. Do not breathe vapours. Wear protective gloves. Take precautionary measures against static discharge. IF SWAL-LOWED: Immediately call a POISON CENTER or doctor. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POI-SON CENTER or doctor if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/ container in accordance with local/ regional/ national/ international regulations.

Additional specifications:

Repeated exposure may cause skin dryness or cracking.

Product contains:

Naphtha, hydrotreated heavy



08/2016

Please beware of: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. The liabil-ity of WEPOS for defective products and any claims for damages whatsever is limited to the purchase price of the products. WEPOS shall not be liable for any consequential damages. No other warranty or representation is made or implied.

WEPOS Chemie GmbH • Textilstr. 2 • 41751 Viersen

Tel.: +49 (0) 2162 - 26 62 69 0 • Fax: +49 (0) 2162 - 26 62 69 8 • Email: info@wepos-chemie.de • www.wepos.de