

# Technical Datasheet

Art.-Nr. 2020203252



## WEPOS Oil Stain Remover

### Description

Dissolves and removes oil stains, oil grime, greasy and oil-like contaminations, also of mineral or synthetic origin. Gel-like consistency ensures long adhesion and effect of the active ingredients. Thus also for deep and old oil stains. For all absorbent and non-absorbent surfaces. For garages, driveways, roads, workshops, motor vehicles, etc.

### Effect:

Dissolves and removes oil stains, oil contamination, greasy and oily contamination, also of a mineral or synthetic based origin. Gel-like consistency ensures long-lasting adhesion to surfaces and long working-in times of the active substances. For this reason, also suitable for older or deep-seated marks and stains.

### Application:

For all absorbent and non-absorbent substrates made of natural stone, artificial stone, cement screeds, concrete floors, glass, tiles, metal, glazed and unglazed ceramic surfaces, clinker, plaster. For garages, entrance ways, streets, pavements, workshops, tools, machines, motor vehicles.

### Direction of use:

The surface to be treated must be dry. Apply a generous layer of the oil stain remover to the contaminated surface and distribute with a brush or broom into the stain. Then allow to work-in for several hours according to the level of contamination (best over night). A light layer of powder forms which can be removed. Repeat the process in the case of older and already resinous or deep-seated marks in the substrate.

Use is according to the type of contamination and the absorbent nature of the substrate. Sufficient for about 5-7m<sup>2</sup>.

### Important:

Not suitable for asphalt and synthetic surfaces. In the case of dark stone surfaces, slightly lighter powder residues may remain in the pores after use. These disappear by themselves over time or can be removed with Wepos Grease, Wax and Dirt Remover.

### Technical Informations

- Density: 0,76 g/ml
- PH: n. a.
- colour: clear liquid
- smell: characteristic

### Safety instruction:

Harmful

Flammable.

Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Keep out of the reach of children.

Do not breathe spray.

Avoid contact with skin and eyes.

Use only in well-ventilated areas.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

### Packing unit

500 ml-tin (6 per box)

Please beware of: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. The liability of WEPOS for defective products and any claims for damages whatever is limited to the purchase price of the products. WEPOS shall not be liable for any consequential damages. No other warranty or representation is made or implied.

April/13

WEPOS Chemie GmbH • Textilstr. 2 • 41751 Viersen / Germany

Tel.: +49 (0) 2162/26 62 69-0 • Fax: +49 (0) 2162/26 62 69-8 • Email: [service@wepos-chemie.de](mailto:service@wepos-chemie.de)

▪ [www.wepos-chemie.de](http://www.wepos-chemie.de)