

TECHNICAL DATA SHEET INTEGRAL WATERPROOFER NEW

Issue 1 - September 2014

Description:

Integral Waterproofer New is a liquid admixture designed for use in reducing water absorption and making cement mixes less permeable. It also improves workability of the mortar.

Areas of Use:

Integral Waterproofer New is suitable for use in rendering finishes and pointing mortars. It is also used in reconstructed stone and non-structural concrete members – particularly valuable in:-

- 1. Semi-dry mixes.
- 2. Internal and external rendering.
- 3. Special finishes.
- 4. Pebble dash and Harling
- Rough Cast.Stucco etc.

Advantages:

- 1.Makes renders and mortars water-resistant.
- 2. Improves weathering properties.
- 3. Reduced suction aids pebble dashing larger areas covered easily.
- 4. Surfaces stay cleaner longer.
- 5. Better appearance after rain
- 6. Less likelihood of efflorescence.
- 7. Drying shrinkage, crazing and cracking reduced.
- 8. Improved frost resistance.
- 9. Greatly reduced capillary attraction.

Application:

Integral Waterproofer New is ready for use and is added to the mix at the selected dosage rate. Mix designs will depend on factors such as location and sand gradings. Refer to local standards and codes of practice for guidance.

Limitations:

Do not pre mix with other admixtures. Do not use in structural concrete.

Do not overmix.

Dosage:

1 litre per 50 - 100kg cement.

Packaging:

1 litre x 12 2.5 litre x 8 5 litre x 4 25 litres x singles

Colour:

Pink

Storage:

Stir or shake well before use. Protect from frost.

Shelf Life:

Minimum of 2 years, if stored at normal temperatures.

Health & Safety:

Please refer to health and safety data sheet on Integral Waterproofer New

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below:-

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use, and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com