

ISSUE: 47-2 / 0809

**EXCELLENT  
INITIAL GRAB**

**FIXES ALL TYPES  
OF WALL-COVERING**

**DRIES TO A CLEAR  
SECURE BOND**

**Description:**

PALACE ALL-PURPOSE WALLPAPER ADHESIVE is a traditional easy to mix starch flake type product, containing chemically incorporated anti-mould additives. With excellent easy slip properties, it may be used for all wallpapers including woodchip, washables, vinyls and heavily embossed. Also ideal for applying polystyrene tiles and for use as a size for sealing new plaster walls prior to papering.

**Surface Preparation:**

Surfaces to be covered should be clean, dry & dust free. Highly absorbent walls should be primed with a dilution of 1 part adhesive to 1 part water to stabilise the surface. The priming coat must be allowed to dry before commencing hanging. Do not use this product at temperatures below 10°C.

**Mixing:**

The volume of cold water to use to make the mix appropriate to the type of paper is given as a rough guide by the table below. Sprinkle contents of sachet into water stirring quickly for 30 seconds to disperse, then when mixed to a smooth lump-free paste leave to stand for 3 minutes then stir again thoroughly. The paste is then ready to use.

APPLICATION	Water to use per sachet	Approximate Coverage
Normal wallpapers including woodchip	6 pints / 3.5 litres	4 – 5 rolls
Vinyl wallcoverings, Washables & Novamura	5 pints / 3 litres	4 rolls
Blown vinyl wallcoverings	5 pints / 3 litres	4 rolls
Embossed papers (Anaglypta)	4 pints / 2.5 litres	2 – 2½ rolls
Heavy embossed papers (Supaglypta)	3.5 pints / 3 litres	1¾ – 2 rolls
Polystyrene tiles	4 pints / 2.5 litres	80 sq ft – 20 m <sup>2</sup>
<b>Sizing:</b> When sizing walls before papering, mix contents of sachet into 8 pints (4½ litres) of cold water		

**Application:**

Apply the adhesive liberally by brush or roller onto paper-backed wall-coverings and hang in the normal way to ensure the pattern continuity is maintained from strip to strip. For other types of wall-covering such as polystyrene veneers and Novamura, spread the adhesive directly to the wall and then hang the wall-covering. If any adhesive gets on the decorative surface of the wall-covering, remove immediately with a damp cloth. For paper backed HESSIAN the adhesive should be applied to the paper backing however on bare hessians always apply the adhesive to the wall. Clean tools immediately in water after use.

**Storage & Packaging:**

ALL-PURPOSE WALLPAPER ADHESIVE is supplied in 6 pint and 12 pint sachets and has a storage life of not less than 12 months if kept in dry, un-opened conditions away from frost or elevated temperatures (> 35°C). Consult the ALL-PURPOSE WALLPAPER ADHESIVE material safety data sheet for advice on handling and safety procedures. Should further more specific technical information be required, contact the Palace Technical helpline on 0151 486 6101.

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.