

TECHNICAL DATA SHEET MOSS & MOULD REMOVER

Issue 5 - August 2014

Description: Moss & Mould Remover kills lichen, moss and similar vegetation providing growth free surfaces.

It is used to remove growth on roofs, walls and other external surfaces prior to treatment with

surface finishes.

Application: Apply by brush or low pressure spray and leave for approximately one hour. Clean the surface

using a stiff bristled brush to remove any loose debris and apply a second coat if any growth remains and leave for at least 24 hours. Clean again and wash down, taking care to remove any white deposit, which may have formed. A trial area should be coated to assess the dosage. Do

not apply in wet weather.

Colour: Clear

Coverage Rate: 4-6m²/litre/coat

Container Sizes: 1, 2.5, 5 + 25 litres

Storage: After use, replace can firmly and shake to ensure an airtight seal is obtained. Containers must

be kept sealed and stored under cover away from sources of ignition at temperatures between

8°C and 25°C. Protect from Frost.

Shelf Life: 2 years under good storage conditions in original, unopened containers.

Cleaning of Tools: Clean immediately after use with clean water.

Disposal of

Containers: Do not leave empty containers on site where residue could be a hazard to children, animals or

the environment. Replace lids and remove to a central disposal point.

Health & Safety: Please refer to health and safety data sheet on Moss & Mould Remover

Further Information: In the event of further queries or problems concerning the use of this product, please contact the

address below:-

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use, and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH www.cromar.uk.com Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com