

TECHNICAL DATA SHEET

Date: 28/11/18
 Version: 1002
 Pages: 1

Arc Butyl Tanking Tape

DESCRIPTION

Arc Tanking Tape is a butyl tape laminated with a non-woven polyester fleece.

KEY FEATURES

Good adhesion to a wide range of substrates. Remains flexible throughout its service life. The product is highly conformable. Easy and accurate to use with little waste and no mess. The fleece will accept paint, plaster, cement and adhesives.

USES

For sealing floor-to-wall joints and around drains in wetrooms. For sealing cracks prior to plastering. For sound-deadening applications. For applications to prevent air-leakage.

PERFORMANCE

	UNIT	NOMINAL VALUE	TEST METHOD
Dynamic Shear Adhesion	N/cm ²	12	H15
90° Peel Adhesion	N/cm	8	H48
180° Peel Adhesion	N/cm	9	H41
Specific Gravity	g/cm ³	1.6	H6
Moisture Vapour Transmission Rate	g/m ² /24hr/mm	0.18	ISO9932 / BS ISO 15106
Service Temperature Range	°C	-40 to +90	

INSTRUCTIONS

Surface preparation: All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates. When applying the tape to porous or friable surfaces, it is recommended that the surface be treated with a suitable primer, such as an exterior grade PVA, to seal and stabilise the surface.

Application: Remove the release paper and apply the tape to the substrates to be joined. Take care to avoid rucks in the tape. Roll the tape with a small roller to ensure good adhesion along the whole length of the tape.

Application temperature range: +5oC to +40oC.

Shelf life: 24 months when stored flat in original packaging in cool, dry conditions.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Arc Building Products products are available for sale in accordance with Arc Building Products standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use, and any labour involved is beyond our control. Our warranty is therefore limited to the quality of supplied product.