

**Safety Data Sheet**

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Trade name : A58 RIGID PVC CEMENT ADHESIVE  
Product code : A58  
Type of product : adhesives  
Product group : Trade product

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Intended for general public

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

AKTEK DIŞ TİC. LTD.  
Yeşilbayır mahallesi Şimşir sokak No:20  
34555 İSTANBUL - TURKEY  
T +90 2127711371 - F +90 2127713888  
[info@demsun.com.tr](mailto:info@demsun.com.tr) [info@aktektd.com.tr](mailto:info@aktektd.com.tr) - [www.demsun.com.tr](http://www.demsun.com.tr)

**1.4. Emergency telephone number**

Emergency number : +90 2127715640 (9:00 am - 17:00 pm GMT+2)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixture

Flammable liquids, Category 2 H225 On basis of test data  
Serious eye damage/eye irritation, Category 2 H319 Calculation method  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336 Calculation method

Full text of hazard classes and H-statements : see section 16

**Adverse physicochemical, human health and environmental effects**

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes serious eye irritation.

**2.2. Label elements**

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

: Danger

Hazardous ingredients :

: acetone, propan-2-one, propanone; butanone, ethyl methyl ketone

Hazard statements (CLP) :

: H225 - Highly flammable liquid and vapour  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (CLP) :

: P102 - Keep out of reach of children  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P271 - Use only outdoors or in a well-ventilated area

# A58 RIGID PVC CEMENT ADHESIVE

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0

P280 - Wear eye protection, face protection, protective clothing, protective gloves  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P370+P378 - In case of fire: Use Dry chemical, CO<sub>2</sub>, or water spray or alcohol-resistant foam to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation  
P243 - Take precautionary measures against static discharge

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking  
Security closing plug for children : Not applicable  
Tactile warning : Applicable

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone, propan-2-one, propanone	(CAS No) 67-64-1 (EC no) 200-662-2 (EC index no) 606-001-00-8 (REACH-no) 01-2119471330-49	20 - 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
butanone, ethyl methyl ketone	(CAS No) 78-93-3 (EC no) 201-159-0 (EC index no) 606-002-00-3 (REACH-no) 01-2119457290-43	20 - 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
ethyl acetate	(CAS No) 141-78-6 (EC no) 205-500-4 (EC index no) 607-022-00-5 (REACH-no) 01-2119475103-46	10 - 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause drowsiness or dizziness.  
Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.  
Symptoms/injuries after eye contact : Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

# A58 RIGID PVC CEMENT ADHESIVE

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

A58 RIGID PVC CEMENT ADHESIVE		
EU	Local name	Acetone
EU	IOELV TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	500 ppm
Austria	Local name	Aceton
Austria	MAK (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
Austria	MAK (ppm)	500 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	4800 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	2000 ppm
Belgium	Local name	Acétone
Belgium	Limit value (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	500 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	1000 ppm
Bulgaria	Local name	Ацетон*
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	1400 mg/m <sup>3</sup>
Croatia	Local name	Aceton

# A58 RIGID PVC CEMENT ADHESIVE

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0

Croatia	GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Croatia	GVI (granična vrijednost izloženosti) (ppm)	500 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	3620 mg/m <sup>3</sup>
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	1500 ppm
Croatia	Naznake (HR)	F, Xi EU*
Czech Republic	Local name	Aceton
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	800 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (PEL) (ppm)	337 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	1500 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (NPK-P) (ppm)	632 ppm
Denmark	Local name	Acetone
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	250 ppm
Denmark	Anmærkninger (DK)	E
Estonia	Local name	Atsetoon (2-propanoon)
Estonia	OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	500 ppm
France	Local name	Acétone
France	VME (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
France	VME (ppm)	500 ppm
France	VLE (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
France	VLE (ppm)	1000 ppm
Germany	Local name	Aceton
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	500 ppm
Germany	Remark (TRGS 900)	DFG,EU
Greece	OEL TWA (mg/m <sup>3</sup> )	1780 mg/m <sup>3</sup>
Greece	OEL STEL (mg/m <sup>3</sup> )	3560 mg/m <sup>3</sup>
Hungary	Local name	ACETON
Hungary	AK-érték	1210 mg/m <sup>3</sup>
Hungary	CK-érték	2420 mg/m <sup>3</sup>
Hungary	Megjegyzések (HU)	i; EU1
Ireland	Local name	Acetone
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	500 ppm
Ireland	Notes (IE)	IOELV
Italy	Local name	Acetone
Italy	OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	500 ppm
Latvia	Local name	Acetons (2-propanons, dimetilketons)
Latvia	OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	500 ppm
Lithuania	Local name	Acetonas
Lithuania	IPRV (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	500 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	1000 ppm
Luxembourg	Local name	Acétone
Luxembourg	OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Luxembourg	OEL TWA (ppm)	500 ppm
Malta	Local name	Acetone
Malta	OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	500 ppm
Netherlands	Local name	Aceton
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>

# A58 RIGID PVC CEMENT ADHESIVE

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0

Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
Poland	Local name	Aceton
Poland	NDS (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Portugal	Local name	Acetona
Portugal	OEL TWA (ppm)	500 ppm
Portugal	OEL STEL (ppm)	750 ppm
Romania	Local name	Acetona
Romania	OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	500 ppm
Slovenia	Local name	aceton
Slovenia	OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	500 ppm
Spain	Local name	Acetona
Spain	VLA-ED (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	500 ppm
Spain	Notes	VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.) , VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
Sweden	Local name	Acetone
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	250 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	500 ppm
United Kingdom	Local name	Acetone
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	500 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	3620 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	1500 ppm
Iceland	Local name	Aseton (2-própanón)
Iceland	OEL (8 hours ref) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Iceland	OEL (8 hours ref) (ppm)	250 ppm
Norway	Local name	Aceton
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	295 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	125 ppm
Switzerland	Local name	Acétone
Switzerland	VME (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
Switzerland	VME (ppm)	500 ppm
Switzerland	VLE (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
Switzerland	VLE (ppm)	1000 ppm
Switzerland	Remark (CH)	4x15
Australia	Local name	Acetone
Australia	TWA (mg/m <sup>3</sup> )	1185 mg/m <sup>3</sup>
Australia	TWA (ppm)	500 ppm
Australia	STEL (mg/m <sup>3</sup> )	2375 mg/m <sup>3</sup>
Australia	STEL (ppm)	1000 ppm
USA - ACGIH	Local name	Acetone
USA - ACGIH	ACGIH TWA (ppm)	250 ppm
USA - ACGIH	ACGIH STEL (ppm)	500 ppm
USA - ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI

# A58 RIGID PVC CEMENT ADHESIVE

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment
Environmental exposure controls	: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Beige.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 67 °C
Flash point	: -10 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 150 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.9 g/ml
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: ≈ 9000 mPa.s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: 80.52 %
-------------	-----------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# A58 RIGID PVC CEMENT ADHESIVE

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

#### A58 RIGID PVC CEMENT ADHESIVE

Viscosity, kinematic	10000.00000000 mm <sup>2</sup> /s
----------------------	-----------------------------------

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR)	: 1133
UN-No. (IMDG)	: 1133
UN-No. (IATA)	: 1133
UN-No. (ADN)	: 1133
UN-No. (RID)	: 1133

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: ADHESIVES
Proper Shipping Name (IMDG)	: ADHESIVES
Proper Shipping Name (IATA)	: Adhesives
Proper Shipping Name (ADN)	: ADHESIVES
Proper Shipping Name (RID)	: ADHESIVES



# A58 RIGID PVC CEMENT ADHESIVE

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0

Transport document description (ADR)	: UN 1133 ADHESIVES, 3, III, (D/E)
Transport document description (IMDG)	: UN 1133 ADHESIVES, 3, III
Transport document description (IATA)	: UN 1133 Adhesives, 3, III
Transport document description (ADN)	: UN 1133 ADHESIVES, 3, III
Transport document description (RID)	: UN 1133 ADHESIVES, 3, III

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3



#### IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3



#### IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3



#### ADN

Transport hazard class(es) (ADN)	: 3
Danger labels (ADN)	: 3



#### RID

Transport hazard class(es) (RID)	: 3
Danger labels (RID)	: 3



### 14.4. Packing group

Packing group (ADR)	: III
---------------------	-------



# A58 RIGID PVC CEMENT ADHESIVE

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0



Packing group (IMDG)	: III
Packing group (IATA)	: III
Packing group (ADN)	: III
Packing group (RID)	: III

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 640E
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:  
Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

#### - Transport by sea

Special provisions (IMDG)	: 223, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.
MFAG-No	: 127;128

#### - Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344

# A58 RIGID PVC CEMENT ADHESIVE

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0

PCA limited quantity max net quantity (IATA) : 10L  
PCA packing instructions (IATA) : 355  
PCA max net quantity (IATA) : 60L  
CAO packing instructions (IATA) : 366  
CAO max net quantity (IATA) : 220L  
Special provisions (IATA) : A3  
ERG code (IATA) : 3L

### - Inland waterway transport

Classification code (ADN) : F1  
Special provisions (ADN) : 640E  
Limited quantities (ADN) : 5 L  
Excepted quantities (ADN) : E1  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 0

### - Rail transport

Classification code (RID) : F1  
Special provisions (RID) : 640E  
Limited quantities (RID) : 5L  
Excepted quantities (RID) : E1  
Packing instructions (RID) : P001, IBC03, LP01, R001  
Special packing provisions (RID) : PP1  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T2  
Portable tank and bulk container special provisions (RID) : TP1  
Tank codes for RID tanks (RID) : LGBF  
Transport category (RID) : 3  
Special provisions for carriage – Packages (RID) : W12  
Colis express (express parcels) (RID) : CE4  
Hazard identification number (RID) : 30

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances

VOC content : 80.52 %

#### 15.1.2. National regulations

##### Germany

VwVwS Annex reference : Water hazard class (WGK) 1, low hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

# A58 RIGID PVC CEMENT ADHESIVE

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/12/2015

Revision date: 1/22/2016

Supersedes: 3/12/2015

Version: 1.0

SZW-lijst van mutagene stoffen	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: None of the components are listed

### Denmark

Classification remarks	: Emergency management guidelines for the storage of flammable liquids must be followed
Recommendations Danish Regulation	: Young people below the age of 18 years are not allowed to use the product

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking

### SDS EU DEMSUN

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*