



# Concentrated Mortar Plasticiser

## CONCENTRATED FOR PERFECT MORTAR

Date: 07 November 2018

Fact Sheet No.: TDS01468

### YOUR SMART ADVANTAGES

- Resin based formula
- Measuring chamber for accurate dose
- Improves the workability of mortar

### USES

Bostik Concentrated Mortar Plasticiser (formerly known as Cementone Concentrated Mortar Plasticiser) improves the workability and freeze thaw resistance of mortar without the addition of lime. It is suitable for use in mortars for bricklaying, pointing, blockwork and rendering.

The integral measuring chamber means accurate, controlled dosage. Bostik Concentrated Mortar Plasticiser conforms to EN 934-3.

### PRODUCT CHARACTERISTICS

Colour	Dark Brown
Form	Thin liquid
Specific Gravity	1.0 approx.
Composition	Concentrated resin solution
Product Code	30806663 1 litre x 6 30612312 1 litre x 6 (EN/PL/RO) 30612314 1 litre x 6 (FR/ES/PT)
Storage/Shelf Life	Store and transport securely in an upright position. Ensure the cap is fully closed. Store for up to 12 months from date of manufacture in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +25°C and out of direct sunlight. Protect from frost.

### TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +40°C
Coverage	A litre bottle is sufficient to plasticise 85 – 125 mixes based upon 25kg of cement

### DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Concentrated Mortar Plasticiser refer to the relevant Health & Safety Data Sheet, available at [www.bostik.com/uk](http://www.bostik.com/uk).

### PREPARATION

This product has been designed to work with Portland cement: CEM I and Portland-fly ash cement: CEM II/B-V. For other types of cement e.g. Portland-limestone CEM II/A-LL it is recommended that a small trial is carried out to ascertain the optimum mix ratios as cement and sand types can vary.

IMPORTANT: Do not use in concrete which is structural i.e. load bearing, reinforced, pre-stressed or steam cured. Work should not be carried out at temperatures below +5°C or when temperatures are expected to fall below this. Ensure materials and procedures comply with the appropriate standards. Do not exceed ratios stated. Do not overmix. Do not use with other admixtures. Do not add to lime based mixes. Do not use with high alumina, sulphate resisting or extra rapid hardening cement. Not suitable for floor screeds. Ensure the substrate is strong enough to support the weight of any render being applied.

1. Ensure that all components of the mix are above 5°C.
2. Sands and aggregate should be dry for best results.
3. Shake the container before use and remove the lid on the cup on the top of the bottle.

### APPLICATION

4. Squeeze the bottle until the liquid in the cup rises to the correct level, 8 – 12ml per 25kg of cement is recommended for most uses. Do not overdose.

5. Add to the gauging water at the appropriate dosage and mix to ensure good dispersal.
6. Add this solution to the sand/cement mix to obtain the mortar consistency required.
7. When using Bostik Concentrated Mortar Plasticiser less water is usually required.
8. Replace the lid on cup when finished.

#### CLEANING

9. Clean tools and equipment with water immediately after use.

#### PRECAUTIONS IN USE

This product has been designed to work with Portland cement: CEM I and Portland-fly ash cement: CEM II/B-V. For other types of cement e.g. Portland-limestone CEM II/A-LL it is recommended that a small trial is carried out to ascertain the optimum mix ratios as cement and sand types can vary.

IMPORTANT: Do not use in concrete which is structural i.e. load bearing, reinforced, pre-stressed or steam cured. Work should not be carried out at temperatures below +5°C or when temperatures are expected to fall below this. Ensure materials and procedures comply with the appropriate standards. Do not exceed ratios stated. Do not overmix. Do not use with other admixtures. Do not add to lime based mixes. Do not use with high alumina, sulphate resisting or extra rapid hardening cement. Not suitable for floor screeds. Ensure the substrate is strong enough to support the weight of any render being applied.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.com/uk](http://www.bostik.com/uk) for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Concentrated Mortar Plasticiser, available at [www.bostik.com/uk](http://www.bostik.com/uk).

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



**CONSTRUCTION PRODUCT REGULATION  
DECLARATION OF PERFORMANCE**

**No: TDS01468**

Product Description: **Bostik Concentrated Mortar Plasticiser**

Product Code: **5000403109862, 5010591004122 & 3549212479909**

Intended Use: **For Use as an Air Entraining/Plasticising  
Admixture for Masonry Mortar**

Manufacturer: **Bostik Ltd**  
Contact Address: **Ulverscroft Road  
Leicester  
LE4 6BW**

System of Assessment: **System 2+**

Harmonised Standard: **EN934-3: 2009 + A1:2012**

**BSi 0086 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued the certificate of conformity of the factory production control.**

Declared Performance:

Essential Characteristics	Performance	Harmonised technical specification
Max chloride content	< 0.1% by mass	<b>EN934-3: 2009 + A1:2012</b>
Max alkali content	1 % by mass	
Corrosion behaviour	<b>NPD Contains components only from EN934-1:2008 Annex A.1</b>	
Dangerous substances	<b>See safety data sheet</b>	

The performance of the product Bostik Concentrated Mortar Plasticiser 5000403109862, 5010591004122 & 3549212479909 is in conformity with the declared performance shown in the table above.

This declaration of performance is issued under the sole responsibility of Bostik Ltd.

**Signed for and on behalf of Bostik Ltd by:**

**Name:** Marrienne Drayton

**Function:** Quality Manager

**Signature:**



**Date:** February 2018

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	<a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>