

# Technical Data Sheet

Date of compilation: 20/10/2022

## ARC STABILISING SOLUTION

### DESCRIPTION

Arc Stabilising Solution -  
Quick drying superior polymer emulsion.

Arc Stabilising Solution is a specially formulated flexible copolymer emulsion with excellent adhesion & hydrophobic properties, which penetrates deeply into dusty/chalky and badly weathered surfaces to leave a stable sound base for subsequent decoration with paint/wallpaper/tiling etc. Suitable for both interior and exterior use over plaster, rendering, pebbledash, stucco, existing painted surfaces, brickwork, blockwork etc.

- Stabilises and binds interior and exterior friable surfaces prior to overcoating.
- Seal and bonds together chalky, dirty and weathered surfaces.
- Leaves a stable base for overpainting with most paints.



### DIRECTIONS FOR USE

All friable and loose material must be removed by a stiff bristled brush and scraping. Any fungal growth should be treated with Moss & Mould Remover; applied liberally by brush or low pressure pneumatic spray. Allow 24 hours and remove all debris, before applying Arc Stabilising Solution. Normally only one coat of Stabilising Solution is necessary and this must be brushed well into the surface as it is extremely important that the solution is completely absorbed, and that a surplus of the material does not lie on the surface. Treated surfaces should be allowed to dry for at least 16 hours before recoating.

### COVERAGE

On smooth surfaces 25-30m<sup>2</sup> per 5 litres. On rough textured surfaces or those that have a high suction, the coverage will be much reduced.

### DRYING TIME

4 - 8 hours, depending on atmospheric conditions. Allow 16 hours before recoating with masonry paints.

### HEALTH & SAFETY

For information and precautions, refer to the safety data sheet.

# Technical Data Sheet

*Date of compilation: 20/10/2022*

## ARC STABILISING SOLUTION

### NOTE

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Full information and advice is freely available from our Technical Services Department e-mail [technical@arcbuildingproducts.ie](mailto:technical@arcbuildingproducts.ie). Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.