

# Technical Data Sheet

Date of compilation: 02/08/2023

## ARC DRIVE REVIVER

### DESCRIPTION

Arc Drive Reviver is a high-performance coating specially formulated to make existing asphalt and tarmac look like new. It restores colour and provides a tough, durable finish which protects from weathering, oil and petrol spills and unsightly plant/weed growth.

- Restores colour
- Seals against water and common spills
- Helps prevent moss and weed growth
- Fast-drying



### PREPARATION

All surfaces must be dry, clean and free from dust, dirt or debris. For best results clean the tarmac by power washing (using lower pressure to prevent damage). Carry out any necessary repairs using a suitable crack repair or Cold lay pothole repair. Do not apply if it is raining or if rain is forecast within 6-12 hours. If algae or green growth has been present, a pre-treatment with Arc Algae & Greenslime Remover is recommended after cleaning and before sealing. Ensure all cleaning products have been rinsed off and surface dried before application.

It is always recommended to carry out a trial on an inconspicuous area to check appearance, finish and suitability.

### APPLICATION

Stir well before and periodically during use. Do not dilute. Apply by brush or roller in an even coat across the entire surface. For best results, apply using a long pile roller in long even strokes. Protect surrounding areas from splashes or overspray. Apply in 2 coats allowing 2-4 hours between coats. Do not allow puddles to form, particularly on textured surfaces, and do not apply in thick layers. Drying time for the final coat will be 2-4 hours depending on conditions. Drying and re-coat times will take longer at lower temperatures and when humidity is high.

### CLEANING

Clean all equipment immediately after use with clean water and detergent. Once dried, sealer will be very difficult to remove from absorbent surfaces.

# Technical Data Sheet

Date of compilation: 02/08/2023

## ARC DRIVE REVIVER

### LIMITATIONS

Do not apply if ambient, air or surface temperature is below 5°C. Do not use externally if rain is imminent (within 6 hours). Do not use over tarmac or asphalt that is less than 3 months old. Do not subject to vehicular traffic within 6 hours of application. At lower temperatures or during damp conditions drying times will be significantly extended. Always check surface is dry and tack free before trafficking. Oil, petrol or chemical spills should be removed as quickly as possible with warm water, detergent and a clean cloth. Do not use a high-pressure spray to clean Driveway Reviver. For use on domestic paths and driveways only. It is the user's responsibility to determine suitability for use. If in any doubt, contact Technical Services for advice.

### TECHNICAL DATA

Appearance	Black slightly viscous liquid
Density	1.0 - 1.1 kg/L
Application Temperature	5 - 30°C
Coverage	6 – 8 m <sup>2</sup> per litre per coat depending on surface
Drying Times (dependent on site conditions)	Overcoat time – within 2-4 hours Light Foot traffic – after 2-4 hours Vehicle Traffic – after 6-12 hours (note it is recommended to wait 24 hours before parking on surface)
Finish	Black low-sheen finish

### HEALTH AND SAFETY

See MSDS for full information.

### NOTE

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Full information and advice is freely available from our Technical Services Department e-mail [technical@arcbuildingproducts.ie](mailto:technical@arcbuildingproducts.ie). Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.